

All rights reserved. Any disclosure or reproduction to a third person is submitted to an authorization.

DEFINITION	4 lug cap for vacuum sealing on threaded ring with the following designation:	FD 138D								
PROFILED PANEL	TNV Flat (no gradin) smooth wall without safety Button / TNV									
SIZES	Please refer to drawing ET70H18TNV at the bottom of the page.									
METAL	<p>Category: tin steel Thickness: 0,16 mm Tinning: 2.8/2.8 g/m²</p> <p>All the metal characteristics comply to the European standard EN 10202</p>									
COMPOUND (P27)	<p>Food contact compound PVC ESBO suitable for non-fatty products and pasteurisation heat treatments up to 100°C.</p> <p>Nominal compound thickness 0.8 mm +/- 0.20 mm</p>									
INTERIOR PROTECTION (2WHPN)	For fairly corrosive and corrosive products: 1 operation of base coat BPA NI and PFAS NI + 1 operation of white organosol varnish BPA NI and PFAS NI									
PROTECTION AND EXTERIOR DECORATION	VARNISH GOLD+CLEAR									
DECLARATION OF CONFORMITY	Please refer to declarations of conformity									
PACKAGING (weights are given with ± 10%)	<p>Average weight of a cap: 13,3 g Gross average weight of a carton: 8,1 kg Number of caps/carton: 550 (in plastic bags)</p> <table border="1"> <thead> <tr> <th>Number of cartons / pallet</th> <th>Number of caps / pallet</th> <th>Gross average weight</th> <th>Pallet size</th> </tr> </thead> <tbody> <tr> <td>30</td> <td>16500</td> <td>243</td> <td>800 X 1 200 X 2 220 mm</td> </tr> </tbody> </table>		Number of cartons / pallet	Number of caps / pallet	Gross average weight	Pallet size	30	16500	243	800 X 1 200 X 2 220 mm
Number of cartons / pallet	Number of caps / pallet	Gross average weight	Pallet size							
30	16500	243	800 X 1 200 X 2 220 mm							
STORAGE CONDITIONS AND DLUO	Please refer to Caps user guide for the Massilly group regarding storage									
USE CONDITIONS	Please refer to Caps user guide for the Massilly group regarding caps and their relevant use.									
DRAWING ET70H18TNV										