

All rights reserved. Any disclosure or reproduction to a third person is submitted to an authorization.

DEFINITION	4 lug cap for vacuum sealing on threaded ring with the following designation:	NF EN ISO 9100-5 06-2005 /GME 20-03 (GPI 2010)								
PROFILED PANEL	RTO Regular Twist Off / RTO									
SIZES	Please refer to drawing ET43H9RTO at the bottom of the page.									
METAL	<p>Category: tin steel Thickness: 0,14 mm Tinning: 2.8/2.8 g/m²</p> <p>All the metal characteristics comply to the European standard EN 10202</p>									
COMPOUND (P27)	<p>Food contact compound PVC ESBO suitable for non-fatty products and pasteurisation heat treatments up to 100°C.</p> <p>Nominal compound thickness 0.8 MM +/- 0.20 mm</p>									
INTERIOR PROTECTION (2WHPN)	For fairly corrosive and corrosive products: 1 operation of base coat BPA NI and PFAS NI + 1 operation of white organosol varnish BPA NI and PFAS NI									
PROTECTION AND EXTERIOR DECORATION	VARNISH WHITE+CLEAR									
DECLARATION OF CONFORMITY	Please refer to declarations of conformity									
PACKAGING (weights are given with ± 10%)	<p>Average weight of a cap: 4,4 g Gross average weight of a carton: 15,8 kg Number of caps/carton: 3400 (in plastic bags)</p> <table border="1"> <thead> <tr> <th>Number of cartons / pallet</th> <th>Number of caps / pallet</th> <th>Gross average weight</th> <th>Pallet size</th> </tr> </thead> <tbody> <tr> <td>30</td> <td>102000</td> <td>473</td> <td>800 X 1 200 X 2 220 mm</td> </tr> </tbody> </table>		Number of cartons / pallet	Number of caps / pallet	Gross average weight	Pallet size	30	102000	473	800 X 1 200 X 2 220 mm
Number of cartons / pallet	Number of caps / pallet	Gross average weight	Pallet size							
30	102000	473	800 X 1 200 X 2 220 mm							
STORAGE CONDITIONS AND DLUO	<p>Please refer to Caps user guide for the Massilly group regarding storage</p> <p>Stacking prohibited.</p>									
USE CONDITIONS	Please refer to Caps user guide for the Massilly group regarding caps and their relevant use.									
DRAWING ET43H9RTO										